

## **CM35**

CM35 is designed for workshop use. CM35 capacity is same as in CM30 but it comes with manual foot pedal. CM35 is easy to use and it comes with a fume exhaust connection.

3-phase and 1-phase electric configurations available. Please also see product cards for other CM30/35 configurations.

| TECHNICAL DATA                 |                |
|--------------------------------|----------------|
| Max. hose size (inch) 1)       | 2 / 1 1/4      |
| Diameter (blade) external (mm) | 300x3          |
| Diameter (blade) internal (mm) | 30             |
| Max. hose OD (mm)              | 70             |
| Exhaust outlet OD (mm)         | 60             |
| Motor Power (kW) 2)            | 3.0/2.2        |
| Motor Power (HP) 2)            | 4.0/2.9        |
| Velocity, 50Hz (rpm)           | 2750           |
| Velocity, 60Hz (rpm)           | 3370           |
| DIMENSIONS (LxWxH)             |                |
| mm                             | 712x562x1127   |
| inch                           | 28.0x22.1x44.4 |
| WEIGHT                         |                |
| kg/lbs                         | 74/162.8       |

Hydraulic hose, 1-2 wire / 4 wire
 3-phase / 1-phase



| STANDARD FEATURES                        |               |
|--|---------------|
| Toothed blade (part no 12297) Foot pedal |               |
| OPTIONS                                  |               |
| Smooth blade (part no 12319)             |               |
|  |               |
|  |               |
|  |               |
|  |               |
|  |               |
| NIN POWER                                | INN-POWER     |
| Toothed blade                            | Smooth blade  |
| as a standard feature.                   | as an option. |



