

P60SCC

LARGE OPENING

Workshop crimper for large camlock -style couplings with increased opening diameter. Ideal machine for small to mid-range industrial hoses.


This model turns hydraulics off to conserve energy, and to reduce workplace noise levels whenever the machine is idle.

SCC control brings smartness to workshop crimpers via connectivity and visual user interface, including step crimping as a standard feature. Optional single foot pedal can be connected to workshop SCC models.

TECHNICAL DATA

ILCI INICAL DATA	
Max crimping dia (mm/inch) ¹⁾	124/4.88
Max crimping dia with master dies (mm/inch)	150/5.9
Max crimping force (kN)	2600
Max crimping force (tonnage)	260
Cycle time 10 mm ²⁾	5.8
Hydraulic hose size (inch)	2 1⁄2 *
Industrial hose size (inch)	4.88 *
Die set series	32/140
Max opening (mm) 3)	+64
Max opening without dies (mm)	204
Master die D/L (mm)	140/120
Master die D/L (inch)	5.52-4.73
Motor Power (kW/HP)	4 / 5.5
Oil tank volume	80
DIMENSIONS (LxWxH)	
(mm)	865x553x871
(inch)	34.1x21.8x34.3
WEIGHT (KG/LBS)	
298/656	
* ACCORDING TO THE FIT	TING.

Foot pedal as an option.



With standard dies. Crimping range can be 1) increased with special dies. Theoretical with 10 mm cycle. 2)

Maximum opening is the total die travel. Add this value to the minimum crimping diameter of the die set used. The result is the maximum opening of the machine with die set in place. 3)

ABSOLUTE QUALITY
` ADE IN
FINLAND

CONTROL			
SCC (5" touch	screen) *		
STANDAR	D FEATI	JRES	
Adapter dies (p Mechanical ba		,	o 720194)
OPTIONS			
Foot pedal (pa Mirror (part no Electrical back Tool base with Tool rack with QuickChange- * MS-control als	720200) stop device QuickChan QuickChang tool (part no	e (part no 7 ge-tool (par ge-tool (par	rt no 720198)
DIE SET 1			
DieSetNo	D (mm)	L (mm)	Crimp. range (mm 84 0-92 0
			Crimp. range (mr 84.0-92.0 92.0-100.0

10000/01	• •		0 110 0210	
18860/92	92	110	92.0-100.0	
18860/100	100	110	100.0-108.0	
18860/108	108	110	108.0-116.0	
18860/116	116	110	116.0-124.0	

DIE SET 32-SERIES

DieSetNo	D (mm)	L (mm)	Crimp. range (mm)
18506/10	10	55	10.0-12.0
18506/12	12	55	12.0-14.0
18506/14	14	55	14.0-16.0
18506/16	16	55	16.0-19.0
18506/19	19	55	19.0-22.0
18506/22	22	70	22.0-26.0
18506/26	26	70	26.0-30.0
18506/30	30	70	30.0-34.0
18506/34	34	75	34.0-39.0
18506/39	39	75	39.0-45.0
18506/45	45	90	45.0-51.0
18506/51	51	90	51.0-57.0
18506/57	57	100	57.0-63.0
18506/63	63	110	63.0-69.0
18506/69	69	110	69.0-75.0
18506/74	74	110	74.0-80.0
18506/78	78	110	78.0-87.0
In addition to the standard die sets, a wide range of special die sets is available on request.			



